



# LED Dimmable Recessed Retrofits

TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

### Limitless options for the following applications:

- Dimmable 6", 5" & 4" downlight applications

### Great features and benefits:

- 120W, 85W, 75W, 65W and 50W BR40/BR30/R20 downlight replacement options
- Excellent color consistency (CRI)
- Smooth, uniform dimming from 100% - 0.5%
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- Available in 2700K, 3000K, 4100K and 5000K
- Easy installation — pigtail and spring clips



4" Dimmable HiCRI Recessed Retrofit



5/6" Dimmable HiCRI Recessed Retrofit



4" Dimmable Recessed Retrofit



5/6" Dimmable Recessed Retrofit



LED  
we know light.™





# LED Dimmable Recessed Retrofits Specifications

<b>LED</b>	35,000 hours average rated life, 120 volts
------------	--

## Applications:

Ideal for dimmable 6", 5" & 4" downlight applications



Perfect for retrofit or new construction recessed downlight applications

## Features and Benefits

- 5/6" unit ideal for replacing dimmable 65W, 85W and 120W incandescent alternatives in 5" and 6" recessed cans
- 4" unit ideal for replacing 50W and 75W incandescent alternatives in a 4" recessed can
- Excellent Color Consistency and CRI
- Smooth, uniform dimming
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- UL approved for damp locations
- Easy installation and integrated trim
- Shatter Resistant



LDRACCGU24 – GU24 Adapter

Catalog Number	
Notes	Type




## Specifications

	14W	11W	10W	9W
Recessed Downlight Size:	5", 6"	5", 6"	4"	4"
Input Line Voltage:	120 VAC	120 VAC	120 VAC	120 VAC
Input Power	14 W	11 W	10 W	9 W
Input Line Frequency	50/60HZ	50/60HZ	50/60HZ	50/60HZ
Lamp Life (Rated)	35,000 hrs	35,000 hrs	35,000 hrs	35,000 hrs
Minimum Starting Temp	-30°C	-30°C	-30°C	-30°C

IC-rated for direct contact with insulation



- LED11DR5627K
- LED11DR5630K
- LED11DR5641K
- LED11DR5650K
- LED14DR5627K
- LED14DR5630K
- LED14DR5641K
- LED14DR5650K



- LED10DR427K
- LED10DR430K
- LED10DR435K
- LED10DR441K
- LED10DR450K



- L11DR56D3527K95
- L11DR56D3530K95



- L9DR4D3527K95
- L9DR4D3530K95



**5 YEAR WARRANTY\***

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP FEB 2018/WF104303





# LED Dimmable Recessed Retrofits Specifications

Smooth Uniform Dimming

## 5/6" Recessed Retrofits

Item #	ENERGY STAR rated	Description	Life Hours	Replacement	Voltage	Wattage	Lumens	LPW	CCT	CRI	Case Qty
<b>Downlight Retrofits compatible with 5/6" recessed cans</b>											
LED14DR5627K	★	LED 14W 5/6" Recessed Downlight - 2700K	35,000	120	120	14	1250	89.3	2700K	80	6
LED14DR5630K	★	LED 14W 5/6" Recessed Downlight - 3000K	35,000	120	120	14	1300	92.9	3000K	80	6
LED14DR5641K	★	LED 14W 5/6" Recessed Downlight - 4100K	35,000	120	120	14	1300	92.9	4100K	80	6
LED14DR5650K	★	LED 14W 5/6" Recessed Downlight - 5000K	35,000	120	120	14	1350	96.4	5000K	80	6
LED11DR5627K	★	LED 11W 5/6" Recessed Downlight - 2700K	35,000	75	120	11	800	72.7	2700K	80	6
LED11DR5630K	★	LED 11W 5/6" Recessed Downlight - 3000K	35,000	75	120	11	850	77.3	3000K	80	6
LED11DR5641K	★	LED 11W 5/6" Recessed Downlight - 4100K	35,000	75	120	11	900	81.8	4100K	80	6
LED11DR5650K	★	LED 11W 5/6" Recessed Downlight - 5000K	35,000	75	120	11	950	86.4	5000K	80	6
<b>Hi CRI Downlight Retrofits compatible with 5/6" recessed cans</b>											
L11DR56D3527K95**	★	LED 11W 5/6" Recessed Downlight - 2700K	35,000	65	120	11	700	63.6	2700K	90	6
L11DR56D3530K95**	★	LED 11W 5/6" Recessed Downlight - 3000K	35,000	65	120	11	750	68.2	3000K	90	6

## 4" Recessed Retrofits

<b>Downlight Retrofits compatible with 4" recessed cans</b>											
LED10DR427K	★	LED 10W 4" Recessed Downlight - 2700K	35,000	75	120	10	750	75.0	2700K	80	6
LED10DR430K	★	LED 10W 4" Recessed Downlight - 3000K	35,000	75	120	10	750	75.0	3000K	80	6
LED10DR435K		LED 10W 4" Recessed Downlight - 3500K	35,000	75	120	10	620	62.0	3500K	80	6
LED10DR441K	★	LED 10W 4" Recessed Downlight - 4100K	35,000	75	120	10	800	80.0	4100K	80	6
LED10DR450K	★	LED 10W 4" Recessed Downlight - 5000K	35,000	75	120	10	800	80.0	5000K	80	6
<b>Hi CRI Downlight Retrofits compatible with 4" recessed cans</b>											
L9DR4D3527K95**	★	LED 9W 4" Recessed Downlight - 2700K	35,000	50	120	9	550	61.1	2700K	90	6
L9DR4D3530K95**	★	LED 9W 4" Recessed Downlight - 3000K	35,000	50	120	9	550	61.1	3000K	90	6

### Accessory

LDRACCGU24      GU24 Adapter

\*JAB Compliant

+All Plastic Body



**5 YEAR WARRANTY\***

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP FEB 2018/WF104303



# CREATING BEAUTY

TCP has a **20-year history in energy-efficient lighting.**

Thanks to our **cutting edge technology** and manufacturing

expertise, we have shipped billions of high quality lamps and our

**integrated technology** and manufacturing

provides **expedited time-to-market.** With TCP, you can

count on unique lighting products designed to meet very specific needs—

lighting that transforms your surroundings and envelopes you in warmth—

**lighting that generates beauty** with every flip of the switch.

# LED

For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | F: 877-487-0516